

EDUCATION AFFILIATES TENANT IMPROVEMENT FOR MEDVANCE INSTITUTE

MEDVANCE INSTITUTE of PORT ST. LUCIE, FLORIDA in the EAST PORT PLAZA

PROJECT DESCRIPTION



BUILDING



SIZE. FUNCTIONALITY. LOCATION AND CODE COMPLIANCE. ALL DISCREPANCIES SHALL BI REPORTED TO THE ARCHITECT PRIOR TO SUBMITTING A BID. THE BID SHALL INCLUDE ALI ITEMS REQUIRED FOR COMPLETE, PROPERLY FUNCTIONING BUILDING SYSTEMS.

GENERAL NOTES

- GENERAL RESPONSIBILITIES
- 1. Each contractor and subcontractor shall visit the site and examine existing conditions to determine the extent of the work. It shall be the responsibility of each contractor to thoroughly examine and verify existing conditions and make allowances for them prior to bidding.
- 2. General Contractors and subcontractors shall review drawings prior to bidding and construction and report any discrepancies to the architect prior to the bid.
- 3. General Contractor shall verify all dimensions and report any discrepancies to the architect.
- 4. This project shall conform to the latest edition to the governing building code. and all other Federal, State, County, and local codes, ordinances, rules and regulations in effect. All those codes and regulations shall take precedence over the drawings. 5. Dimensions as indicated on the drawings shall take precedence over scaling of the drawings.
- 6. These drawings DO NOT show every minor detail of construction. The contractor shall furnish and install all items required for a complete, properly functioning building system, and shall fulfill all
- requirements for all equipment to be placed in proper working order. Contractor's bid shall include all items and work to assure compliance with the most with the most stringent requirements of governing building codes and regulations.
- 7. Each contractors and subcontractors shall be responsible for the safety and well being of his employees and shall strictly follow all construction safety regulations, including OSHA.
- 8. All contractors and subcontractors shall be currently licensed in the state, county, and local cities as required. Provide copies of licenses to Owner prior to commencement of work.
- 9. All contractors and subcontractors shall carry the minimum workman's compensation, liability, and automobile insurance required by the state and higher if required by the owner. Provide insurance certificates to Owner before to commencement of work.
- 10. Should the scope of work for any reason, for any reason not be fully indicated on the scope of drawings, the contractor shall immediately contact the architect for clarifications.
- 11. The work shall be limited to the scope indicated in the drawings and specifications. If any additional work is performed without owners approval, it shall be at the sole expense of the
- 12. Contractor shall pay for and obtain all permits and secure all certificates of inspections and certificates of occupancy that are required by governing jurisdiction.
- 13. Any deviation and/ or substitution from the information provided herein shall be submitted to the architect for his approval prior to the performance of the work.
- 14. The Contractor shall coordinate all tenant or Owner supplied items, and incorporate it into the Contractor's work schedule. Verify scope of such items prior to bid submittal.
- 15. The Contractor shall include into bid and provide all temporary utilities required for the work
- 16. Each contractor shall protect its own work and work of other contractors. All conflicts to be resolved by the General Contractor. The General Contractor shall be responsible for the full coordination of work by all trades. Any damages resulting from lack of coordination, lack of work protection shall be the sole responsibility of the General Contractor, that includes all damages from weather, water and dust.
- 17. The Contractor shall expedite and schedule the delivery of long lead items to conform with the
- 18. The Contractor shall warrant and guarantee all work, all component performance, and all material for one year from the date shown on the certificate of occupancy.

- B. SCHEDULES, ORGANIZATION AND COORDINATION
- 1. Contractor shall be responsible for scheduling and implementing all work so as not to disrupt or inconvenience adjacent property users.
- C. CLEANING REQUIREMENT
- 1. The jobsite shall be maintained in a safe and neat condition at all times. Broom cleaning shall be performed as needed to avoid debris build up.
- 2. All building materials shall be stored in a safe and organized manner so as not to interfere with work of other trades.
- 3. At project completion, the jobsite shall be fully cleaned and turned over to the occupant ready for them to move in and begin operating without any additional work or cleaning. This requires all surfaces to be cleaned with appropriate cleaning solutions, vacuumed, and waxed/ sealed as appropriate. All windows, mirrors, hardware, cabinetry, and walls finished and fixtures shall be cleaned.
- ROOF PENETRATIONS
- 1. Any roof penetrations such as vents, chimneys, equipment curbs, and skylights required shall be flashed and sealed to be water tight. If roof is under warranty or bonded, the general contractor shall hire the warranting roof or bonding company to perform all roof modification work.
- CODE NOTES
- 1. Provide U.L. Rated Fire Extinguishers (Min. rating of 10 lb.ABC)located within 50 foot travel distance from any point within the tenant space. Obtain Fire Marshall approval of locations. At a minimum provide two extinguishers; one located near front exit in an obvious location and the second located in the rear or secondary exit in an obvious location. All extinguishers to have
- 2. All penetrations in fire rated assemblies shall be sealed with materials approved by governing agencies meeting U.L. (or equal) specifications including installation systems. all ducts penetrating fire rated assemblies shall receive fire dampers.
- 3. All doors shall have hardware per N.F.P.A standards. All exit door locks shall have thumb latches requiring less than 180 degrees turn. Entry locks shall not require key operation in the direction of
- 4. Adhere to building standards for work affecting common areas.
- 5. All doors in rated walls to be U.L. labeled, both door and jamb, with U.L. closers.
- 6. Fire resistive standards for interior finishes shall be required per NFPA 101. Documentation shall be provided to the architect prior to final inspection.
- 7. All new walls, ceiling grids, lights, conduits, pipes, ducts and wires, whether new or existing, to be braced, strapped, and/or supported per code, and shall meet U.L. and manufacturer
- 8. All fixtures and Hardware shall comply with ADA 2010 standards and State building codes with
- 9. Testing for the presence of hazardous materials shall be the Owners responsibility.
- 10. All glass doors and within 4'-0" of doors shall be tempered.

DRAWING LIST

ARCHITECTURAL: **COVER SHEET**

CODE SHEET FIRST FLOOR DEMOLITION FIRST FLOOR PLAN

CEILING PLAN - FIRST FLOOR INTERIOR ELEVATIONS

CASEWORK DETAILS A9.1 FINISH AND DOOR SCHEDULE

COVER SHEET MECHANICAL FLOOR PLAN MECHANICAL DEMOLITION FLOOR PLAN MECHANICAL

COVER SHEET ELECTRICAL FLOOR PLAN DEMOLITION SIM LABS E1.1 FLOOR PLAN POWER SIMLABS E1.2 FLOOR PLAN LIGHTING SIMLABS

ELECTRICAL SCHEDULES, DETAILS, AND DIAGRAMS

MECHANICAL SCHEDULES AND DETAILS

PLUMBING:

P0.1 **COVER SHEET PLUMBING** FLOOR PLAN PLUMBING DEMOLITION

P1.1 FLOOR PLAN PLUMBING P2.1 PLUMBING SCHEDULES AND DETAILS

FIRE PROTECTION:

COVER SHEET FIRE PROTECTION FLOOR PLAN FIRE PROTECTION

DESIGN TEAM

ARCHITECT:


RCG ARCHITECTS, INC. 509 SOUTH EXETER STREET, SUITE 300 BALTIMORE, MD 21202 PHONE: 410.685.7033

MEP ENGINEER:

FAX: 410.783.0090

Siegel, Rutherford, Bradstock & Ridgway, Inc. 757 Frederick Road - Suite 300 Catonsville, Maryland 21228 PHONE: 410.869.7282


KEY PLAN



RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090

SUI

PROJECT NO:




- OCCUPANTS USING EXIT / EXIT CAPACITY

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090 MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc. 757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282 SHE SUI MEDVANCE INSTITUTE
PORT ST. LUCIE
ADMIN/FAC. AREA & SIM SUI

PROJECT NO: 1225

Ш

DATE: 03/18/2013 DRAWING NO:




RCG ARCHITECTS 509 South Exeter Street Baltimore, MD 21202 phone: 410.685.7033

fax: 410.783.0090

757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282

DATE: 03/18/2013



RCG ARCHITECTS 509 South Exeter Street Suite 300


Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090


MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc. 757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282

EDUCATION


PROJECT NO: 1225 DATE: 03/18/2013

DRAWING NO: A1.1





— ACOUSTICAL LAY-IN PANEL



EDUCATION AFFILIATES

PROJECT NO: 1225

DRAWING NO:

SHEET:

DATE: 03/18/2013

GENERAL NOTES:

RCP LEGEND

ALL CEILINGS AT 9'-0" AFF U.N.O.
 CORRIDOR BULKHEADS AT 8'-6" AFF U.N.O.

- DOWNLIGHT

- SUPPLY DIFFUSER


- LINEAR SLOT DIFFUSER

C - EXISTING CAMERAS TO BE RELOCATED

- 2x2 LIGHT

- 2x4 LIGHT

- RETURN




RCG ARCHITECTS 509 South Exeter Street Suite 300

Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090

MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc. 757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282

EDUCATION AFFILIATES

PROJECT NO: 1225



RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090 MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc. 757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282 SUIT

PROJECT NO: 1225 DATE: 03/18/2013 DRAWING NO:


EDUCATION


						DOOR	SCHEDULE			
Mark	To Room: Name	Width	Height	Door Type	Door Material	Frame Type	Frame Material	Hardware	Signage	Comments
119	HALL	3' - 0"	7' - 0"	Α	WD / GLS	Α	HM	EX	G2	EXISTING DOOR TO REMAIN
119A	INTERVIEW	3' - 0"	7' - 0"	В	WD / GLS	Α	HM	7A	G2	
119B	INTERVIEW	3' - 0"	7' - 0"	В	WD / GLS	Α	HM	7A	G2	
119C	DEBRIEF	3' - 0"	7' - 0"	В	WD / GLS	Α	HM	1A	G2	
120	NURSING	4' - 4"	7' - 0"	E	WD / GLS	С	HM	EX	G2	RELOCATE EXISTING DOOR AND HARDWARE
120A	SIM LAB	4' - 4"	7' - 0"	E	WD / GLS	С	HM	1A	G2	
120B	SIM LAB	4' - 4"	7' - 0"	Е	WD / GLS	С	HM	1A	G2	
120C1	CONTROL RM	3' - 0"	7' - 0"	Α	WD	Α	HM	1A	G2	
120C2	CONTROL RM	3' - 0"	7' - 0"	DD	WD	D	HM	8	G2	
120D	PREP RM	3' - 0"	7' - 0"	В	WD / GLS	Α	HM	1A	G2	
141A	COPY	3' - 0"	7' - 0"	В	WD / GLS	Α	HM	1A	G2	
141B	FAC OFFICE	3' - 0"	7' - 0"	В	WD / GLS	Α	HM	1A	G1	
141C	FAC OFFICE	3' - 0"	7' - 0"	В	WD / GLS	Α	HM	1A	G1	
141D	FAC OFFICE	3' - 0"	7' - 0"	В	WD / GLS	Α	HM	1A	G1	
141E	FAC OFFICE	3' - 0"	7' - 0"	В	WD / GLS	Α	HM	1A	G1	
141F	FAC OFFICE	3' - 0"	7' - 0"	В	WD / GLS	Α	MH	1A	G1	


					FINI	ISH SCH	EDULE			
Number	Name	Floor Finish	Base	Wall Primary	Wall Feature	Ceiling	Countertops	Cabinets	Comments	Area
119	HALL	CPT-1	VCB4	PNT1	-	ACT	-	-		82 SF
119A	INTERVIEW	CPT-1	VCB4	PNT1	PNT2	ACT				69 SF
119B	INTERVIEW	CPT-1	VCB4	PNT1	PNT2	ACT				69 SF
119C	DEBRIEF	CPT-1	VCB4	PNT1	PNT2	ACT				140 SF
120	NURSING	ETR/ MATCH EX	MATCH EX	PNT1	PNT2	ACT	PLAM1	PLAM2	NEW VCT AT ENTRY AS INDICATE ON PLANS ONLY	921 SF
120A	SIM LAB	VCT4	VCB3	PNT1		ACT				117 SF
120B	SIM LAB	VCT4	VCB3	PNT1		ACT				116 SF
120C	CONTROL RM	CPT-1	VCB2	PNT7		ACT	PLAM1	PLAM2		109 SF
120D	PREP RM	VCT1	VCB1	PNT1	PNT2	ACT	PLAM1	PLAM2		81 SF
141A	COPY	CPT-1	VCB4	PNT1	PNT2	ACT	PLAM1	PLAM2		72 SF
141B	FAC OFFICE	CPT-1	VCB4	PNT1	PNT2	ACT				106 SF
141C	FAC OFFICE	CPT-1	VCB4	PNT1	PNT2	ACT				105 SF
141D	FAC OFFICE	CPT-1	VCB4	PNT1	PNT2	ACT				106 SF
141E	FAC OFFICE	CPT-1	VCB4	PNT1	PNT2	ACT				106 SF
141F	FAC OFFICE	CPT-1	VCB4	PNT1	PNT2	ACT				107 SF
	1	1	-	1	1		1		,	2306 S


	L DOORS TO BE LOCATED 6" FROESS OTHERWISE NOTED.	МСС	RNER
DOO	R HARDWARE KEY		
SET	FUNCTION	OP	TIONS
1	OFFICE FUNCTION	Α	WALL STOP
2	CLASSROOM/CORRIDOR	В	FLOOR STOP
3	CLASSROOM SECURITY	С	OVERHEAD STOP
4	EGRESS FUNCTION	D	CLOSER
5	STOREROOM FUNCTION	Е	GASKET
6	STOREROOM FUNCTION PAIRS		
7	PASSAGE FUNCTION		
8	SLIDING		


DOOR GENERAL NOTES
















1) ALL SIGNS ARE TO BE MOUNTED IN ACCORDANCE WITH ADA REQUIREMENTS. 2) SUBMIT SHOP DRAWINGS OF PROPOSED NEW SIGNS PRIOR TO FABRICATION.

5 SIGNAGE PLACEMENT 1/4" = 1'-0"



G1 (GENERAL ROOM SIGN)

6 SIGNAGE 6" = 1'-0"



(BASE BID)

3 FRAME TYPES 1/4" = 1'-0"

G2 (GENERAL ROOM SIGN)

1) ARCHITECT TO PROVIDE FINISH FLOOR PLAN TO INDICATE WALLS TO RECIEVE FEATURE PAINT COLOR AND PATTERN OF VCT 2) ALL HM FRAMES TO BE PAINTED PNT8 U.O.N.

FINISHES GENERAL NOTES

FINISH SCHEDULE KEY

FLOOR FINISHES

3) ALL DOORS TO BE HARDWOOD MAPLE VENEER U.O.N.

4) ALL GWB CEILINGS AND BULKHEADS TO BE PNT U.O.N.

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033

CPT1 CARPET 1: SHAW, BLOG TEKLOK 5A126, VINTAGE TAUPE fax: 410.783.0090 CPT2 CARPET 2: SHAW, PRAIRIE TILE 59525, SIBERIAN SEA 23485 CPT3 CARPET 3: SHAW, ESCAPE TILE 59457, CENTRIC 54485 VCT1 VINYL COMPOSITION TILE 1:ARMSTRONG, STANDARD EXCELON, BLUE CLOUD 51933 VINYL COMPOSITION TILE 2:ARMSTRONG, STANDARD EXCELON, SERENE BLUE 51881 VINYL COMPOSITION TILE 3:ARMSTRONG, STANDARD EXCELON, COLORADO STONE 57506 VINYL COMPOSITION TILE 4:ARMSTRONG, STANDARD EXCELON, BLUEBERRY 51881 VINYL COMPOSITION TILE 5:ARMSTRONG, STANDARD EXCELON, WASHED LINEN 51810 VCT6 VINYL COMPOSITION TILE 6:ARMSTRONG, STANDARD EXCELON, LITTLE GREEN APPLE 51866 SOLID RESILIENT TILE 1'ARMSTRONG, NATIONAL CREATIONS ARBORART, NOUVEAU MAPLE HONEY TP-042 **CONC** SEALED CONCRETE MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc. **WALL BASE**

757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282 VCB1 VINYL COVE BASE 1: JOHNSONITE, TRADITIONAL WALL BASE, NAVY BLUE 18 VINYL COVE BASE 2: JOHNSONITE, TRADITIONAL WALL BASE, GREY 48 VCB3 VINYL COVE BASE 3: JOHNSONITE, TRADITIONAL WALL BASE, BLUE LAGOON 92 VINYL COVE BASE 1: JOHNSONITE, TRADITIONAL WALL BASE, BROWN 47 VINYL COVE BASE 1: JOHNSONITE, TRADITIONAL WALL BASE, SHORELINE 280 VINYL COVE BASE 1: JOHNSONITE, TRADITIONAL WALL BASE, SANDALWOOD 45 PAINT 1: GENERAL WALL COLOR, SHERWIN WILLIAMS, WHITE DUCK SW7010, EGGSHELL PAINT 2: ACCENT TO PNT1 AND PNT4, SHERWIN WILLIAMS, UNIVERSAL KHAKI SW6150, EGGSHELL PAINT 3: LRC WALL COLOR, SHERWIN WILLIAMS, PEARLY

PAINT 4: ACCENT PNT3, PRIMARY WALL COLOR IN STUDENT COMMONS, SHERWIN WILLIAMS, LANTERN LIGHT SW6687, EGGSHELL PNT5 PAINT 5: ACCENT TO PNT3, SHERWIN WILLIAMS, EXCITING ORANGE SW6647, EGGSHELL PAINT 6: ACCENT TO PNT1, SHERWIN WILLIAMS, VAST SKY SW6506, EGGSHELL

WHITE SW7009, EGGSHELL

PAINT 7: CONTROL ROOM WALL COLOR, SHERWIN WILLIAMS, FOLKSTONE SW6005, EGGSHELL PAINT 8: HOLLOW METAL FRAME COLOR, SHERWIN WILLIAMS, COROTHANE I-MIO ALUMINUM B65S14, MATTE

VINYL WAINSCOT

VINYL WAINSCOT 1: THROUGHOUT CORRIDOR, ACROVYN, WALL PANEL, MUSHROOM 305. WAINSCOT UP TO 48" AFF. ACCESSORIES FOR INSTALLATION AS SPECIFIED. VINYL WAINSCOT 2: TOILET ROOMS, ACROVYN, WALL PANEL, PUMICE 858. WAINSCOT UP TO 48" AFF. ACCESSORIES FOR INSTALLATION AS SPECIFIED.

CEILINGS ACOUSTICAL CEILING PANELS: ARMSTRONG, FISSURED, SQUARE LAY-IN 15/16" (SEE RCP FOR SIZE) PAINTED GYPSUM WALL BOARD ON LIGHT GUAGE METAL **ETR** EXISTING TO REMAIN

CASEWORK FINISHES PLAM1 PLASTIC LAMINATE 1: WILSONART GILDED MESH 4912-38

PLAM1B | CHEMICAL RESISTANT PLASTIC LAMINATE 1: WILSONART GILDED MESH 4912-60 (WITH CHEMSURF FINISH) **PLAM2** PLASTIC LAMINATE 2: WILSONART SHEER MESH 4876-38

PLAM3 PLASTIC LAMINATE 3: NOT USED

PLAM4 | PLASTIC LAMINATE 4: WILSONART SMOKY TOPAZ 4589-60 WOOD VENEER: MAPLE WOOD VENEER ON MDF CORE, CLEAR FINISH

PROJECT NO:


EDUCATION

FINISH AND SCHEDULE

SUIT

DATE: 03/18/2013

DRAWING NO:



GENERAL REQUIREMENTS

- 1. REFER TO THE SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS OF THIS PROJECT.
- 2. BID PHASE: IT IS THE CONTRACTOR'S RESPONSIBILITY TO REVIEW ALL DOCUMENTS TO INCLUDE PLANS AND SPECIFICATIONS FOR THE ARCHITECTURAL AND OTHER WORK UNDER OTHER DIVISIONS THAT CAN AFFECT THE WORK OF THIS DIVISION. THE CONTRACTOR SHALL ISSUE A FORMAL REQUEST FOR INFORMATION FOR CLARIFICATIONS OF ANY DISCREPANCIES IN THE DOCUMENTS PRIOR TO FINAL BID SUBMISSION.
 - 3. PRE-CONSTRUCTION: IT IS THE CONTRACTOR'S RESPONSIBILITY TO REVIEW ALL REVISED DOCUMENTS TO INCLUDE ARCHITECTURAL PLANS AND WORK UNDER OTHER DIVISIONS THAT CAN AFFECT THE WORK OF THIS DIVISION. THIS INCLUDES REVIEW OF ALL ADDENDUMS, REVISIONS AND SHOP DRAWINGS THAT AFFECT THE WORK OF THIS DIVISION. THE CONTRACTOR SHALL NOTIFY THE A/E TEAM OF ANY DISCREPANCIES PRIOR TO FINAL

SPECIAL CONDITIONS

- A. <u>DEMOLITION COORDINATION</u>:
- 1. REFER TO ARCHITECTURAL DEMOLITION PLANS FOR ADDITIONAL DEMOLITION REQUIREMENTS.
- 2. REFER TO ARCHITECTURAL PLANS AND/OR SUPPLEMENTAL DOCUMENTS FOR CONSTRUCTION PHASE SEQUENCE REQUIREMENTS FOR OCCUPIED SPACES AFFECTED BY THE WORK.
- 3. NOTIFY THE LANDLORD OF ANY WORK THAT MAY DISRUPT OTHER AREAS OUTSIDE OF THE WORK AREA.
- B. WORK IN EXISTING CEILINGS:
- 1. REFER TO ARCHITECTURAL CEILING PLAN AND RELATED DETAILS FOR CEILING CONDITIONS, ADDITIONAL REQUIREMENTS, AND SYSTEM INSTALLATION COORDINATION. REFER TO ARCHITECTURAL PLANS FOR AREAS TO BE DEMOLISHED AND PROVIDED WITH NEW CEILING FINISHES. ALL OTHER AREAS ARE EXISTING CEILINGS TO REMAIN.
- WHERE EXISTING CEILING ARE DISTURBED BY THE NEW WORK, THE EXISTING CEILING GRID AND TILES SHALL BE RE-USED AND PROTECTED DURING CONSTRUCTION AND REINSTALLED IN KIND. SECTIONS OF THE CEILING SYSTEM SHALL BE TEMPORARILY REMOVED AND REPLACED IN KIND, WHERE NEEDED, TO ACCOMMODATE THE WORK. DAMAGED CEILING SYSTEMS SHALL BE REPLACED WITH NEW SYSTEMS AS NEEDED.
- 3. EXISTING DISTURBED DRYWALL CEILINGS SHALL BE PATCHED, REPAIRED, AND FINISHED TO MATCH EXISTING CONDITIONS.
- 4. COORDINATE SCOPE OF WORK IN EXISTING CEILINGS WITH GENERAL CONTRACTOR AT TIME OF BIDS AND PRIOR TO START OF WORK.
- C. <u>EQUIPMENT COORDINATION:</u>
- 1. REFER TO ARCHITECTURAL EQUIPMENT PLANS, FURNITURE PLANS, ELEVATIONS, CASEWORK ELEVATIONS AND OTHER RELATED PLANS FOR ADDITIONAL MEP PROVISIONS.

DRAW	ING LIST
SHEET #	SHEET TITLE
M0.1	COVER SHEET MECHANICAL
M1.0	FLOOR PLAN MECHANICAL DEMOLITION
M1.1	FLOOR PLAN MECHANICAL
M2.1	MECHANICAL SCHEDULES AND DETAILS

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090

MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc. 757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282

COVER SHEET MECHANICAL


MEDVANCE INSTITUTE
PORT ST. LUCIE
ADMIN/FAC. AREA & SIM SUITE
9164 US Highway 1 South
Port St. Lucie, FL 34928

PROJECT NO:

1225 DATE: 03/18/2013 DRAWING NO:

SHEET:

OF:



RCG

RCG ARCHITECTS
509 South Exeter Street
Suite 300
Baltimore, MD 21202
phone: 410.685.7033
fax: 410.783.0090

LOID ON

MEP ENGINEER:
Siegel, Rutherford, Bradstock & Ridgway, Inc.
757 Frederick Road - Suite 300
Catonsville, Maryland 21228
(410) 869-7282


FLOOR PLAN
MECHANICAL
DEMOLITION

MEDVANCE INSTITUTE
PORT ST. LUCIE
ADMIN/FAC. AREA & SIM SUITE
9164 US Highway 1 South
Port St. Lucie, FL 34928

ROJECT NO:

1225
DATE: 03/18/2013
DRAWING NO:

| M1.0



FLOOR PLAN - MECHANICAL

SCALE: 1/4" = 1'-0"

0 1' 2' 4' 8'

RCG

RCG ARCHITECTS
509 South Exeter Street
Suite 300
Baltimore, MD 21202
phone: 410.685.7033
fax: 410.783.0090


MEP ENGINEER:
Siegel, Rutherford, Bradstock & Ridgway, Inc.
757 Frederile, Maryland 21228
(410) 869-7282

OWNER'S REPRESENT
APPROVAL
AL
AL

FLOOR PLAN
MECHANICAL

MEDVANCE INSTITUTE
PORT ST. LUCIE
ADMIN/FAC. AREA & SIM SUITE
9164 US Highway 1 South
Port St. Lucie, FL 34928


PROJECT NO: 1225



FLEXIBLE DUCT RUN-OUT SUPPORT DETAIL

NO SCALE

- FLEXIBLE DUCT SHOULD EXTEND STRAIGHT FOR SEVERAL INCHES FROM RECTANGULAR DUCT CONNECTION BEFORE BENDING.
- 2. FLEXIBLE DUCT SHOULD NOT EXCEED 8'-0" IN LENGTH. USE RIGID ROUND DUCTWORK WHEN RUNOUTS EXCEED 8'-0".



RECTANGULAR BRANCH DUCT TAKE-OFF DETAIL

NO SCALE

		AIR DEVICE SCHEDULE							
MARK	SYSTEM	MANUFACTURER & MODEL NO.	REMARKS						
MARK	TYPE	MANOFACTORER & MODEL NO.	REMARKS						
Α	SUPPLY		FURNISH WITH OFF WHITE POWDER COAT						
A	DIFFUSER	PERFORATED, INDIVIDUALLY ADJUSTABLE CURVED BLADES, 24"x24" MODULE.	FINISH.						
В	RETURN	"PRICE" No. 'PDDR' ALL STEEL CONSTRUCTION FLUSH FACE,	FURNISH WITH OFF WHITE POWDER COAT						
В	DIFFUSER	PERFORATED, 24"x24" MODULE.	FINISH.						
С	SUPPLY	REUSE EXISTING SUPPLY DIFFUSER. DO NOT REUSE ANY	CLEAN EXISTING DIFFUSER OF ANY						
	DIFFUSER	EXISTING DIFFUSERS DAMAGED DURING DEMOLITION.	DEBRIS AND DIRT PRIOR TO INSTALLING.						
D	RETURN	REUSE EXISTING SUPPLY DIFFUSER. DO NOT REUSE ANY	CLEAN EXISTING DIFFUSER OF ANY						
U	DIFFUSER	EXISTING DIFFUSERS DAMAGED DURING DEMOLITION.	DEBRIS AND DIRT PRIOR TO INSTALLING.						
_	SUPPLY	"PRICE" No. '520D' DOUBLE DEFLECTION BARS, OPPOSED	FURNISH WITH OFF WHITE POWDER COAT						
E	REGISTER	BLADE DAMPER	FINISH.						
_	RETURN	"PRICE" No. '530' 34" BLADE SPACING, STEEL	FURNISH WITH OFF WHITE POWDER COAT FINISH.						
F	REGISTER	CONSTRUCTION.	FINION.						

								<u>E</u>	XIST	ΓING	PAC	KAG	E H	EA1	ГРИМР	ROOF	TOP L	INIT SC	HEDULE	(FOR IN	FORMATIO	N O	NLY)
MARK	AREA SERVED	REFRIGERANT	EER	C.F.M.	E.S.P. IN W.G.	COOLIN MB		HEATING MBT 25°	CAP UH 45°	ELEC HEAT KW	COOLING TONS	EVAP	ORATOR AMPS	FAN HP	COMPRESSOR R.L.A.	CONDENSER FANS	OUTSIDE AIR C.F.M.		TROLS STAGES HEAT	MANUFACTURER & MODEL NO.	V-P-H M.C.A.	MAX. FUSE	REMARKS
ExRTU 5	CLASS ROOM	R-410A	10.9	1200	0.90"		37.1			7.5	3.0	_	2.0	0.5	1@5.8	1@1.1	250	1	1	"LENNOX" No. 'KHB036S4D-3G	, 480-3-60 22	25	FURNISH WITH 14" HIGH FULL PERIMETER ROOF CURB, MOTORIZED OUTSIDE AIR DAMPER AND INTAKE HOOD, MERV 8 FILTERS, LOW AMBIENT KIT, PROGRAMMABLE TOUCH SCREEN 7-DAY THERMOSTAT W/FOUR TIME PERIODS A DAY, AUTOMATIC CHANGE OVER, OUTDOOR TEMP SENSOR, LOCKING COVER, ELECTRIC HEAT PACKAGE, WALL MOUNTED CO2 SENSOR.
ExRTU 9	NURSE FACILITY	R-410A	11.0	2400	0.90"	55.9	73.5	47.7	68.9	15.0	6.0	1216	3.0	1.5	1@9.7	1@1.5	400	1	1	"LENNOX" No. 'KHB072S4B-3G	480-3-60 40	40	FURNISH WITH 14" HIGH FULL PERIMETER ROOF CURB, MOTORIZED OUTSIDE AIR DAMPER AND INTAKE HOOD, MERV 8 FILTERS, LOW AMBIENT KIT, PROGRAMMABLE TOUCH SCREEN 7-DAY THERMOSTAT W/FOUR TIME PERIODS A DAY, AUTOMATIC CHANGE OVER, OUTDOOR TEMP SENSOR, LOCKING COVER, ELECTRIC HEAT PACKAGE, WALL MOUNTED CO2 SENSOR.
ExRTU 10	NURSE SKILLS	R-410A	10.9	1200	0.90"	28.5	37.1	23.2	34.6	7.5	3.0	_	2.0	0.5	1@5.8	1@1.1	225	1	1	"LENNOX" No. 'KHB036S4D—3G	, 480-3-60 22	25	FURNISH WITH 14" HIGH FULL PERIMETER ROOF CURB, MOTORIZED OUTSIDE AIR DAMPER AND INTAKE HOOD, MERV 8 FILTERS, LOW AMBIENT KIT, PROGRAMMABLE TOUCH SCREEN 7-DAY THERMOSTAT W/FOUR TIME PERIODS A DAY, AUTOMATIC CHANGE OVER, OUTDOOR TEMP SENSOR, LOCKING COVER, ELECTRIC HEAT PACKAGE, WALL MOUNTED CO, SENSOR.
ExRTU 16a	LRC	R-410A	11.0	2400	0.90"	55.9	73.5	47.7	68.9	15.0	6.0	1216	3.0	1.5	1@9.7	1@1.5	520	1	1	"LENNOX" No. 'KHB072S4B—3G	, 480-3-60 40	40	FURNISH WITH 14" HIGH FULL PERIMETER ROOF CURB, MOTORIZED OUTSIDE AIR DAMPER AND INTAKE HOOD, MERV 8 FILTERS, LOW AMBIENT KIT, PROGRAMMABLE TOUCH SCREEN 7-DAY THERMOSTAT W/FOUR TIME PERIODS A DAY, AUTOMATIC CHANGE OVER, OUTDOOR TEMP SENSOR, LOCKING COVER, ELECTRIC HEAT PACKAGE, WALL MOUNTED CO2 SENSOR.

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090

MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc. 757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282


MECHANICAL SCHEDULES A DETAILS

MEDVANCE INSTITUTE
PORT ST. LUCIE
ADMIN/FAC. AREA & SIM SUITE
9164 US Highway 1 South
Port St. Lucie, FL 34928

PROJECT NO: 1225 DATE: 03/18/2013

SHEET:

DRAWING NO:



GENERAL REQUIREMENTS

- 1. REFER TO THE SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS OF THIS PROJECT.
- 2. <u>BID PHASE:</u> IT IS THE CONTRACTOR'S RESPONSIBILITY TO REVIEW ALL DOCUMENTS TO INCLUDE PLANS AND SPECIFICATIONS FOR THE ARCHITECTURAL AND OTHER WORK UNDER OTHER DIVISIONS THAT CAN AFFECT THE WORK OF THIS DIVISION. THE CONTRACTOR SHALL ISSUE A FORMAL REQUEST FOR INFORMATION FOR CLARIFICATIONS OF ANY DISCREPANCIES IN THE DOCUMENTS PRIOR TO FINAL BID SUBMISSION.
- 3. <u>PRE-CONSTRUCTION:</u>
 IT IS THE CONTRACTOR'S RESPONSIBILITY TO REVIEW ALL REVISED DOCUMENTS TO INCLUDE ARCHITECTURAL PLANS AND WORK UNDER OTHER DIVISIONS THAT CAN AFFECT THE WORK OF THIS DIVISION. THIS INCLUDES REVIEW OF ALL ADDENDUMS, REVISIONS AND SHOP DRAWINGS THAT AFFECT THE WORK OF THIS DIVISION. THE CONTRACTOR SHALL NOTIFY THE A/E TEAM OF ANY DISCREPANCIES PRIOR TO FINAL ROUGH—IN.

SPECIAL CONDITIONS

- A. <u>DEMOLITION COORDINATION:</u>
- REFER TO ARCHITECTURAL DEMOLITION PLANS FOR ADDITIONAL DEMOLITION REQUIREMENTS.
- 2. REFER TO ARCHITECTURAL PLANS AND/OR SUPPLEMENTAL DOCUMENTS FOR CONSTRUCTION PHASE SEQUENCE REQUIREMENTS FOR OCCUPIED SPACES AFFECTED BY THE WORK.
- NOTIFY THE LANDLORD OF ANY WORK THAT MAY DISRUPT OTHER AREAS OUTSIDE OF THE WORK AREA.
- B. WORK IN EXISTING CEILINGS:
- 1. REFER TO ARCHITECTURAL CEILING PLAN AND RELATED DETAILS FOR CEILING CONDITIONS, ADDITIONAL REQUIREMENTS, AND SYSTEM INSTALLATION COORDINATION. REFER TO ARCHITECTURAL PLANS FOR AREAS TO BE DEMOLISHED AND PROVIDED WITH NEW CEILING FINISHES. ALL OTHER AREAS ARE EXISTING CEILINGS TO REMAIN.
- 2. WHERE EXISTING CEILING ARE DISTURBED BY THE NEW WORK, THE EXISTING CEILING GRID AND TILES SHALL BE RE-USED AND PROTECTED DURING CONSTRUCTION AND REINSTALLED IN KIND. SECTIONS OF THE CEILING SYSTEM SHALL BE TEMPORARILY REMOVED AND REPLACED IN KIND, WHERE NEEDED, TO ACCOMMODATE THE WORK. DAMAGED CEILING SYSTEMS SHALL BE REPLACED WITH NEW SYSTEMS AS NEEDED.
- EXISTING DISTURBED DRYWALL CEILINGS SHALL BE PATCHED, REPAIRED, AND FINISHED TO MATCH EXISTING CONDITIONS.
- 4. COORDINATE SCOPE OF WORK IN EXISTING CEILINGS WITH GENERAL CONTRACTOR AT TIME OF BIDS AND PRIOR TO START OF WORK.
- C. <u>EQUIPMENT COORDINATION</u>:
- REFER TO ARCHITECTURAL EQUIPMENT PLANS, FURNITURE PLANS, ELEVATIONS, CASEWORK ELEVATIONS AND OTHER RELATED PLANS FOR ADDITIONAL MEP
- D. <u>MODULAR FURNITURE</u>:

PROVISIONS.

- 1. CONTRACTOR SHALL COORDINATE EXACT LOCATIONS OF POWER AND COMMUNICATIONS FEED POINTS WITH THE FURNITURE SUPPLIER AND TENANT PRIOR TO ROUGH—IN. LOCATIONS ON PLANS ARE FOR CIRCUIT CONFIGURATION ONLY.
- 2. VERIFY ELECTRICAL REQUIREMENTS WITH FURNITURE SUPPLIER.
- 3. VERIFY VOICE/DATA RACEWAY PROVISIONS WITH OWNER'S COMMUNICATIONS VENDOR PRIOR TO ROUGH—IN.
- E. PATIENT CARE GROUNDING:
- REFER TO SUPPLEMENTAL MEDICAL EQUIPMENT PLANS AND RELATED ARCHITECTURAL PLANS FOR ADDITIONAL MEP PROVISIONS AND REQUIREMENTS FOR INCLUSION IN THE FINAL BID.
- 2. IT IS THE CONTRACTOR'S RESPONSIBILITY TO REVIEW ALL DOCUMENTS AND THE EXISTING CONDITIONS PRIOR TO START OF WORK. NOTIFY THE ENGINEER OF ANY DISCREPANCIES WITH EQUIPMENT PROVISIONS PRIOR TO START OF WORK AND
- 3. COORDINATE REQUIREMENTS OF DENTAL CHAIR ROUGH—IN WITH TENANT AND DENTAL EQUIPMENT SUPPLIER PRIOR TO ROUGH—IN.
- 4. ALL POWER & LIGHTING CIRCUITS SERVING PATIENT CARE AREAS SHALL HAVE REDUNDANT GROUNDING CONNECTIONS IN COMPLIANCE WITH NEC 70 ARTICLE 517.13(A) & (B).
- 5. REQUIREMENTS WILL APPLY TO POWER CIRCUITS TO AUTOMATIC FAUCETS WITHIN PATIENT CARE AREAS.

SYMBOL	<u>DESCRIPTION</u>	<u>SYMBOL</u>	DESCRIPTION	<u>P0</u>	WER DISTRIBUTION SYMBOLS		
=	DUPLEX RECEPTACLE - STANDARD, 125 VOLT. 14" A.F.F.	♦	MOTOR CONNECTION. SEE SCHEDULE FOR HP RATING UNLESS NOTED OTHERWISE.	SYMB	OL <u>DESCRIPTION</u>	SYMBOL	DESCRIPTION
₩Н	DUPLEX RECEPTACLE — STANDARD, 125 VOLT. MOUNTED HORIZONTALLY	⋈	CONTROL EQUIPMENT	3/2	25 INDICATES 3 POLE/PHASE, 225A TI	RIP T i	FSS
	(SEE ARCHITECTURAL ELEVATIONS)	Ø	PHOTOCELL — CIRCUIT CONTROLLED AS INDICATED ON PLANS.		(FRAME RATING FOR SWITCH)	··· 🗀	
-	DUPLEX RECEPTACLE — STANDARD, 125 VOLT. 44" A.F.F.		WIRING UP	2/1		RIP L	NFSS
\Rightarrow	DUPLEX RECEPTACLE - GFI PROTECTED, 125 VOLT. 44" A.F.F. AT KITCHEN COUNTER	—	WIRING DOWN		(FRAME RATING FOR SWITCH)	S	CFSS
	AND BATHROOM VANITY, OTHERWISE AT 14" A.F.F.		WIRING CONCEALED ABOVE CEILING OR IN WALL (2 CONDUCTORS + EQUIPMENT GROUND	60		M	METER
= EWC	ELECTRIC WATER COOLER — PROVIDE DEDICATED CIRCUIT WITH GFCI PROTECTION. (VERIFY ELECTRICAL REQUIREMENTS AND MOUNTING HEIGHTS PRIOR TO ROUGH—IN)		MINIMUM UNLESS NOTED OTHERWISE).		→ FUSED SWITCH	7	GROUNDING ELECTRODE
_	DUPLEX RECEPTACLE — WP AND GFI PROTECTED, 125 VOLT. 14" A.F.F.		WIRING BELOW GRADE OR BELOW FINISHED SLAB (Ô" C. — 2#10 + 1#10 EQUIPMENT GROUND MINIMUM UNLESS NOTED OTHERWISE).	▶	CIRCUIT BREAKER	<u>+</u>	GROUNDING ELECTRODE
≔ ⇒ IG	DUPLEX RECEPTACLE — WP AND GFT PROTECTED, 125 VOLT. 14" A.F.F. ORANGE FINISH.	<u></u>	WIRING: NEUTRAL (OVERSIZED TICK), 2 PHASE CONDUCTORS		MOTOR CONNECTION - 3 PHASE		STEP DOWN TRANSFORMER
	DUPLEX RECEPTACLE — PC/COMMUNICATION, 125 VOLT. 14" A.F.F. GRAY FINISH.	"			MOTOR CONNECTION - 1 PHASE		
-	(PROVIDE WITH DEDICATED NEUTRAL PER CIRCUIT)		WIRING: INSULATED EQUIPMENT GROUND CONDUCTOR	<u>FEEDER</u>	LEGEND	<u>EX</u>	ISTING CONDITIONS
=	QUAD OUTLET; ONE STANDARD 125 VOLT DUPLEX RECEPTACLE & ONE 125 VOLT PC DUPLEX RECEPTACLE; MOUNTING HEIGHT AS NOTED		WIRING: INSULATED ISOLATED GROUND (I.G.) CONDUCTOR	<u>DESIGNATIO</u>		DESIGNATION	
	QUAD OUTLET; TWO 125 VOLT DUPLEX RECEPTACLES;		WIRING: INSULATED REDUNDANT GROUND (PER HEALTH FACILITY REQUIREMENTS)	X SETS	QTY. OF PARALLEL SETS (1 SET IF E	BLANK) [] 与 PHANTOM DEVICES TO BE REMOVED
	MOUNTING HEIGHT AS NOTED	│	HOMERUN TO PANEL (SOURCE PANEL & CIRCUIT NUMBERS, AS INDICATED)		── WIRE SIZE IN AWG. •── NEUTRAL SIZE	(N)	NEW EQUIPMENT
$\overline{\bullet}$	SIMPLEX RECEPTACLE — SPECIAL PURPOSE, VERIFY CONFIGURATION. 14" A.F.F.		FLEXIBLE WIRING: CONDUCTORS TO MATCH SUPPLY CIRCUIT	1#xx G →	EQUIPMENT GROUND	(E)	EXISTING EQUIPMENT TO REMAIN
	FLOOR BOX (WITH DUPLEX RECEPTACLE SHOWN). DEVICE TYPE SHALL BE AS INDICATED ON THE DRAWINGS. FLUSH IN FLOOR.				ISOLATED GROUND 	(R)	EXISTING EQUIPMENT RELOCATED
₽c		_	ELECTRICAL PANEL: 120/208 VOLT - SURFACE, RECESSED MOUNTED	-		(X)	EXISTING EQUIPMENT TO BE REMOVED
→ C	DUPLEX RECEPTACLE, 125 VOLT. FLUSH IN CEILING.	<u> </u>	ELECTRICAL PANEL: 277/480 VOLT - SURFACE, RECESSED MOUNTED	ABI	<u>BREVIATIONS</u>		
	VOICE OUTLET. 14" A.F.F.	,	DIAN NOTE DEED TO NOTES ON DRAWING	DESIGNATION	DESCRIPTION	NOTE:	ALL EQUIPMENT SHOWN IS NEW U.N.O.
\triangleright	DATA OUTLET. 14" A.F.F.		PLAN NOTE — REFER TO NOTES ON DRAWING.			MO) NEO	NON EUGED OFEED OMETON
>	COMBINATION VOICE/DATA OUTLET. 14" A.F.F.	\downarrow	EQUIPMENT CONNECTION NOTE - SEE SCHEDULE.		ABOVE FINISHED FLOOR (TO CENTERLINE U CONDUIT	NL NFSS	NON-FUSED SAFETY SWITCH NIGHTLIGHT (24 HOUR OPERATION)
₽	FLOOR BOX DATA OUTLET. FLUSH IN FLOOR			C/B C	CIRCUIT BREAKER	PC	PC/COMMUNICATION OUTLET
	FLOOR BOX COMBINATION VOICE/DATA OUTLET. FLUSH IN FLOOR		SYMBOL INDICATES 24 HOUR LIGHT (NIGHT LIGHT)		COMBINATION FUSED STARTER SWITCH	S-1	SECTION #1 OF 2 SECTION PANEL
♦ I	TELEVISION OUTLET - MATV/CATV SYSTEM. 14" A.F.F.				NCLOSED CIRCUIT BREAKER LECTRIC WATER COOLER (VERIFY MTD.)		(PROVIDE PANEL WITH FEED THRU LUGS)
୕ୢ୷ଠ୳	JUNCTION OR PULL BOX — CEILING, WALL MOUNTED. SIZE PER N.E.C. UNLESS NOTED OTHERWISE.			G E	QUIPMENT GROUND	S-2 SHUNT	SECTION #2 OF 2 SECTION PANEL SHUNT TRIP CIRCUIT BREAKER
\$K,\$P,\$M	SWITCH - KEY OPERATED, PILOT LIGHT, MOTOR RATED				GROUND FAULT INTERRUPTER C/B GROUND FAULT CIRCUIT INTERRUPTER	SP SN	SURGE SUPPRESSOR SUPER NEUTRAL
\$ R	SWITCH - REO-STAT FOR FAN CONTROL				USED SAFETY SWITCH	TG	TRANSFORMER GROUND
C	CONTACTOR: SEE PLANS FOR SPECIFICATIONS				SOLATED GROUND	UNO	UNLESS NOTED OTHERWISE
T	MANUAL THERMAL MOTOR STARTER. SIZE OVERLOAD AS REQUIRED.				MAIN CIRCUIT BREAKER	WP	WEATHERPROOF (NEMA 3R UNO)
TC	TIME CLOCK			MLO N	MAIN LUGS ONLY		
		1					

DRAW	ING LIST
SHEET #	SHEET TITLE
E0.1	COVER SHEET ELECTRICAL
E1.0	FLOOR PLAN DEMOLITION
E1.1	FLOOR PLAN POWER
E1.2	FLOOR PLAN LIGHTING
E2.1	POWER DISTRIBUTION DIAGRAMS
E2.2	ELECTRICAL SCHEDULES. DETAILS, AND DIAGRAMS

RCG

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033

fax: 410.783.0090

Description

No.

MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc. 757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282

APPROVAL

COVER SHEET
ELECTRICAL

MEDVANCE INSTITUTE
PORT ST. LUCIE
ADMIN/FAC. AREA & SIM SUITE
9164 US Highway 1 South
Port St. Lucie, FL 34928

e


PROJECT NO: 1225

DATE: 03/18/2013

DRAWING NO:

SHEET:

E0.1



FLOOR PLAN - DEMOLITION
SIM LABS
SCALE: 1/4" = 1'-0"

0 1' 2' 4'

GENERAL NOTES:

G1) AREA TO REMAIN. MAINTAIN ALL EXISTING POWER, LIGHTING AND TELECOMMUNICATION SYSTEMS.

LIGHTING NOTES:

AREA OF COMPLETE DEMOLITION:
REMOVE ALL LIGHTING FIXTURES AND REINSTALL IN NEW
CEILING CONFIGURATION. REMOVE ALL ASSOCIATED
CONTROLS AND WIRING BACK TO SOURCE PANEL. REUSE
EXISTING LIGHTING CIRCUITS WHERE POSSIBLE. (REFER TO
LIGHTING PLAN FOR NEW LOCATIONS AND WIRING
REQUIREMENTS)

POWER NOTES:

- P1 AREA OF COMPLETE DEMOLITION:
 REMOVE ALL RECEPTACLES, OUTLETS AND ASSOCIATED
 WIRING BACK TO SOURCE PANEL.
- P2 AREA OF SELECTIVE DEMOLITION:
 REMOVE ALL RECEPTACLES AND ASSOCIATED WIRING AT PARTITIONS TO BE DEMOLISHED. MODIFY AND MAINTAIN EXISTING RECEPTACLES CIRCUITS EFFECTED BY THE DEMOLITION. RECONNECT NEW OUTLETS TO EXISTING CIRCUITS (REFER TO POWER PLAN)

TELECOMMUNICATIONS NOTES:

- T1) AREA OF COMPLETE DEMOLITION:
 REMOVE ALL TELECOMMUNICATION OUTLETS AND CABLING BACK TO SOURCE RACK.
- T2 AREA OF SELECTIVE DEMOLITION:
 REMOVE ALL TELECOMMUNICATION OUTLETS AND
 ASSOCIATED CABLING AT PARTITIONS TO BE DEMOLISHED.
 PROVIDE NEW TELECOMMUNICATION OUTLETS AT NEW
 PARTITIONS. (REFER TO POWER PLAN)

DEMOLITION LEGEND

<u>DESIGNATION</u> <u>DESCRIPTION</u>

EXISTING EQUIPMENT TO REMAIN
MAINTAIN EXISTING CONNECTIONS
EXISTING EQUIPMENT TO BE RELOCATED
EXISTING EQUIPMENT TO BE REMOVED

CONSTRUCTION ISSUE 03/18/2013

SRBR No: 13039

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090 MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc. 757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282

PLOOR PLAN
DEMOLITION
SIM LABS

MEDVANCE INSTITUTE
PORT ST. LUCIE
ADMIN/FAC. AREA & SIM SUITE
9164 US Highway 1 South
Port St. Lucie, FL 34928

PROJECT NO:


1225


DATE: 03/18/2013

DRAWING NO:

E1.0


OF:





FLOOR PLAN - POWER

SCALE: 1/4" = 1'-0"



PART PLAN - ELECTRIC ROOM SCALE: 1/4" = 1'-0"0 1' 2' 4'

GENERAL NOTES:

1. ALL ELECTRICAL EQUIPMENT AND DEVICES SHOWN ARE NEW UNLESS NOTED OTHERWISE.

POWER PLAN NOTES:

- (P1) CONNECT RECEPTACLES AND DATA OUTLETS AT VERTICAL HEAD WALL ASSEMBLY. COORDINATE EXACT LOCATIONS, OUTLET QUANTITY, AND MOUNTING HEIGHTS WITH ARCHITECTURAL HEAD WALL DETAIL.
- P2 LOCATE OUTLETS ADJACENT TO SIM LAB BED AS DIMENSIONED ON ARCHITECTURAL HEAD WALL DETAIL.
- P3 CONNECT TO EXISTING POWER CIRCUIT AS INDICATED ON POWER PLAN. CONTRACTOR TO VERIFY EXISTING CIRCUIT AVAILABILITY AND CONNECTED LOAD. PROVIDE NEW 1P, 20A CIRCUIT IN EXISTING PANEL 'P1H' IF EXISTING POWER CIRCUIT IS UNAVAILABLE.
- (P4) RECEPTACLE AND DATA OUTLET MOUNTED BELOW COUNTER. COORDINATE EXACT LOCATIONS AND MOUNTING HEIGHT WITH ARCHITECTURAL ELEVATIONS PRIOR TO ROUGH-IN.
- (P5) CONNECT TO EXISTING POWER CIRCUIT AS INDICATED ON POWER PLAN. PROVIDE DEDICATED NEUTRAL CIRCUIT. CONTRACTOR TO VERIFY EXISTING CIRCUIT AVAILABILITY AND CONNECTED LOAD. PROVIDE NEW 1P, 20A CIRCUIT IN EXISTING PANEL 'P1H' IF EXISTING POWER CIRCUIT IS UNAVAILABLE.
- (P6) PROVIDE POWER AND DATA OUTLET AT 60" AFF FOR LCD DISPLAY. VERIFY MOUNTING HEIGHT AND CONNECTION REQUIREMENTS WITH EQUIPMENT SUPPLIER PRIOR TO ROUGH-IN.
- (P7) PROVIDE FLUSH MOUNTED JUNCTION BOX FOR POWER TO SYSTEMS FURNITURE. FIELD COORDINATE EXACT LOCATION AND REQUIREMENTS PRIOR TO ROUGH-IN. MAKE CONNECTIONS TO FURNITURE AS DIRECTED BY SUPPLIER.
- (P8) PROVIDE FLUSH MOUNTED JUNCTION BOX FOR TELEPHONE/DATA TO SYSTEMS FURNITURE. FIELD COORDINATÉ EXACT LOCATION AND REQUIREMENTS PRIOR TO ROUGH-IN. MAKE CONNECTIONS TO FURNITURE AS DIRECTED BY SUPPLIER.
- (P9) CONNECT TO NEW POWER CIRCUITS AS INDICATED ON POWER PLAN. PROVIDE (3) 1P 20A CIRCUIT BREAKERS WITH DEDICATED NEUTRAL AND (1) 1P 20A CIRCUIT BREAKER WITH ISOLATED GROUND IN EXISTING PANEL
- P10 EXISTING ELECTRICAL EQUIPMENT AND DEVICES IN THIS AREA TO REMAIN. MAINTAIN EXISTING ELECTRICAL CONNECTIONS.
- P11 RELOCATED CAMERA. EXTEND ASSOCIATED WIRING TO NEW CAMERA LOCATION AND MAINTAIN EXISTING CIRCUIT. COORDINATE EXACT LOCATION WITH ARCHITECTURAL REFLECTED CEILING PLAN.

EXISTING CONDITIONS

<u>DESIGNATION</u>		DESCRIPTION
(N)	NEW	EQUIPMENT

(E) EXISTING EQUIPMENT TO REMAIN (R) EXISTING EQUIPMENT RELOCATED EXISTING EQUIPMENT TO BE REMOVED

CONSTRUCTION ISSUE 03/18/2013

SRBR No: 13039

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090 MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc. 757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282

FLOOR PL POWER SIM LABS


SUIT


PROJECT NO:


1225 DATE: 03/18/2013 DRAWING NO:

SHEET:

OF:







LIGHTING PLAN NOTES:

- L1 CONNECT EMERGENCY BATTERY PACK AHEAD OF LOCAL SWITCH CONTROL.
- L2 CONNECT TO EXISTING CORRIDOR LIGHTING CIRCUIT SERVING THIS AREA.
- CONNECT TO EXISTING CORRIDOR NIGHT LIGHTING CIRCUIT SERVING THIS AREA.
- CONNECT TO EXISTING LIGHTING CIRCUIT L1B-1.
 CONTRACTOR TO VERIFY EXISTING CIRCUIT AVAILABILITY
 AND CONNECTED LOAD. CONNECT TO EXISTING 1P, 20A
 SPARE CIRCUIT BREAKER IF EXISTING LIGHTING CIRCUIT IS
 UNAVAILABLE.
- EXISTING LIGHTING IN THIS AREA TO REMAIN. MAINTAIN EXISTING ELECTRICAL CONNECTIONS AND LIGHTING CONTROLS.
- CONNECT TO EXISTING LIGHTING CIRCUIT L1B-7.
 CONTRACTOR TO VERIFY EXISTING CIRCUIT AVAILABILITY
 AND CONNECTED LOAD. CONNECT TO EXISTING 1P, 20A
 SPARE CIRCUIT BREAKER IF EXISTING LIGHTING CIRCUIT IS
 UNAVAILABLE.



RCG ARCHITECTS
509 South Exeter Street
Suite 300
Baltimore, MD 21202
phone: 410.685.7033
fax: 410.783.0090


MEP ENGINEER:
Siegel, Rutherford, Bradstock & Ridgway, Inc.
757 Frederick Road - Suite 300
Catonsville, Maryland 21228
(410) 869-7282

FLOOR PLAN LIGHTING SIM LABS

MEDVANCE INSTITUTE
PORT ST. LUCIE
ADMIN/FAC. AREA & SIM SUITE
9164 US Highway 1 South
Port St. Lucie, FL 34928

PROJECT NO: 1225

OF:



POWER DISTRIBUTION DIAGRAM

SHOP DRAWINGS OF RATED EQUIPMENT).

1. EQUIPMENT IMMEDIATELY DOWN STREAM OF FAULT CURRENT A.I.C. RATING DESIGNATION SHALL BE BRACED FOR THE RATING INDICATED. BRANCH MAINS

SHALL BE U.L. SERIES RATED OR CURRENT LIMITING TYPE FUSES TO REDUCE DOWN STREAM FAULT CURRENT TO 10k A.I.C. OR LESS (SUBMIT

NO SCALE

						PA	NE	L	L1	В	(E)		
	VOLTAGE: 277 / PHASE, WIRE: 3 PH ,					225	AMP	MAIN	C/B				A.I.C.: 14k MOUNTED: SURFAC	E
		C/	В	WIF	RE				WIF	RE	C/E	3		
CKT	SERV ING	Р	TRIP	QTY	AWG	KVA	PH	KVA	QTY	AWG	Р	TRIP	SERV ING	CK
1	LTG-NURSING SKILLS	1	20	2	12	2.5	Α				1	20	SPARE	2
3	LTG-DENTAL LAB	1	20	2	12	1.5	В				1	20	SPARE	4
5	LTG-CLASS RM/X-RAY	1	20	2	12	2.7	С				1	20	SPARE	6
7	LTG-CLASS RM/ LABS	1	20	2	12	2.8	Α						BUSSED SPACE	8
9	LTG-OFFICES	1	20	2	12	2.8	В						BUSSED SPACE	10
11	LTG-CORRIDOR	1	20	2	12	1.5	С						BUSSED SPACE	12
13	LTG-CORRIDOR N.L. (1)	1	20	2	12	1.5	Α						BUSSED SPACE	14
15	LTG-EXTERIOR (2)	1	20	2	12	2.0	В						BUSSED SPACE	16
17	LTG-EXTERIOR N.L. (1)(2)	1	20	2	12	2.0	С						BUSSED SPACE	18
19	LTG-CANOPY	1	20	2	12	2.0	Α						BUSSED SPACE	20
21	SPARE	1	20				В						BUSSED SPACE	22
23	SPARE	1	20				С						BUSSED SPACE	24
25	SPARE	1	20				Α						BUSSED SPACE	26
27	BUSSED SPACE						В						BUSSED SPACE	28
29	BUSSED SPACE						С						BUSSED SPACE	30
31	BUSSED SPACE						Α						BUSSED SPACE	32
33	BUSSED SPACE						В						BUSSED SPACE	34
35	BUSSED SPACE						С						BUSSED SPACE	36
37	BUSSED SPACE				ó .		Α	23.7	3	2	3	100	TRANSFORMER 'T1B'	38
39	BUSSED SPACE						В	21.5						40
41	BUSSED SPACE						С	21.8	1					42

(1) PROVIDE HANDLE LOCK-ON CIRCUIT BREAKER COVER.

(2) VIA TIMECLOCK/CONTACTOR (REFER TO TIMECLOCK/CONTACTOR DETAIL ON SHEET E2.2)

						PA	NE	L	P1	ΙE	(E)		
	VOLTAGE: 120 /	208											A.I.C.: 10k	
	PHASE, WIRE: 3 PH,	4 W				225	AMP	MAIN	C/B				MOUNTED: SURFAC	E
													_	
	111 18000	C/	В	WIF	RE		11 11		WIF	RE	C/E	3	0.000	
CKT	SERV ING	Р	TRIP	QTY	AWG	KVA	PH	KVA	QTY	AWG	P	TRIP	SERVING	CKT
1	REC-X-RAY 156	1	20	2	12	0.5	Α	0.5	2	12	1	20	REC-CLASS 115	2
3	REC-X-RAY 156	1	20	2	12	0.5	В	0.5	2	12	1	20	REC-CLASS 115	4
5	REC-X-RAY 156	1	20	2	12	0.5	O	0.5	2	12	1	20	REC-CLASS 115	6
7	REC-X-RAY 156	1	20	2	12	0.5	Α	0.5	2	12	1		REC-CLASS 115	8
9	REC-X-RAY 156	1	20	2	12	0.5	В	0.5	2	12	1	20	REC-CLASS 115	10
11	REC-X-RAY 157	1	20	2	12	0.5	O	0.5	2	12	1	20	REC-CLASS 115	12
13	REC-X-RAY 157	1	20	2	12	0.5	Α	0.5	2	12	1	20	REC-CLASS 115	14
15	REC-X-RAY 157	1	20	2	12	0.5	В	0.5	2	12	1	20	REC-CLASS 115	16
17	REC-X-RAY 157	1	20	2	12	0.5	С	0.5	2	12	1	20	REC-PREP ROOM 120D	18
19	REC-X-RAY 157	1	20	2	12	0.5	Α	0.5	2	12	1	20	REC-NURSING SKILL 120	20
21	REC-DEBREIF 119C	1	20	2	12	0.5	В	0.5	2	12	1	20	REC-SIM LAB 120B	22
23	REC-INTERVIEW 119 (1)	1	20	2	12	0.5	С	0.5	2	12	1	20	REC-CTRL RM 120C	24
25	RECS-CONTROL RM (1)	1	20	2	12	0.5	Α	0.5	2	12	1	20	REC-CTRL RM 120C (1)	26
27	REC-SIM LAB 120B (1)(2)	1	20	2	12	0.5	В	0.5	2	12	1	20	REC-OFFICE 144	28
29	RECS-DEBRIEF	1	20	2	12	0.5	С	0.5	2	12	1	20	REC-OFFICE 144	30
31	LTG-UNDERCABINET	1	20	2	12	1.5	Α	0.5	2	12	1	20	REC-EWC	32
33	SPARE	1	20				В	0.5	2	12	1	20	REC-X-RAY 156	34
35	REC-SIM LAB 120B	1	20	2	12	0.5	C	1.0	2	12	1	20	REC-X-RAY 156	36
37	PANEL 'P1G'	3	100	4	2	5.5	Α	6.0	4	2	3	100	PANEL 'D'	38
39						5.7	В	5.5						40
41						5.2	C	4.9						42
TOT	AL DEMAND KVA (PER PHAS	E):	A:	16.1	E	3: 14.0		C: 13.4	DE	SIGN K	VA:	48	DESIGN AMPS:	134

* EXISTING ISOLATED GROUND BUS BAR. (1) PROVIDE DEDICATED NUETRAL. (2) ISOLA TED GROUND CIRCUIT.

						PA	NE	L	P ₁	IF				
	VOLTAGE: 120 / PHASE, WIRE: 3 PH ,				٠	225	AMP	MAIN	LUGS	;			A.I.C.: 10k MOUNTED: SURFA	CE
		C/	В	WIF	RE				WIF	RE	C/E	3		Т
CKT	SERVING	Р	TRIP	QTY	AWG	KVA	PH	KVA	QTY	AWG	Р	TRIP	SERVING	CKT
1	REC-SERVER	1	20	3	12	0.8	Α	0.8	2	12	1	20	REC-OFFICE 144	2
3	REC-SERVER	1	20	3	12	0.8	В	0.8	2	12	1	20	REC-OFFICE 151A	4
5	REC-ADMIN. 158	1	20	2	12	0.8	С	0.8	2	12	1	20	REC-OFFICE 152	6
7	REC-ADMIN. 158	1	20	2	12	8.0	Α	0.8	2	12	1	20	REC-RECEPT. 101	8
9	REC-ADMIN. 158	1	20	2	12	8.0	В	0.8	2	12	1	20	REC-RECEPT. 101	10
11	REC-ADMIN. 158	1	20	3	12	8.0	C	0.8	2	12	1	20	REC-OFFICE 158B	12
13	REC-ADMIN. 158	1	20	2	12	8.0	Α	0.8	2	12	1	20	REC-OFFICE 158B	14
15	REC-ADMIN. 158	1	20	2	12	8.0	В	0.8	2	12	1	20	REC-COPY 158C	16
17	REC-ADMIN. 158	1	20	2	12	8.0	C	0.8	2	12	1	20	REC-COPY 158C	18
19	REC-ADMIN. 158	1	20	3	12	8.0	Α	0.8	2	12	1	20	REC-OFFICE 158F	20
21	REC-ADMIN. 158	1	20	2	12	8.0	В	0.8	2	12	1	20	REC-OFFICE 158F	22
23	REC-ADMIN. 158	1	20	2	12	0.8	С	0.8	2	12	1	20	REC-BREAK 147	24
25	REC-ADMIN. 158	1	20	2	12	0.8	Α	0.8	2	12	1	20	REC-BREAK 147	26
27	REC-ADMIN. 158	1	20	3	12	8.0	В	0.8	2	12	1	20	REC-BREAK 147	28
29	UND COUNTER REF RM 147	1	20	2	12	1.0	С	0.8	2	12	1	20	REC-MED 142	30
31	SPARE	1	20				Α	0.8	2	12	1	20	REC-MED 142	32
33	SPARE	1	20				В	0.8	2	12	1	20	REC-MED 142	34
35	SPARE	1	20				С	0.8	2	12	1	20	REC-MED 142	36
37	PANEL 'P1H'	3	100	4	2	3.2	Α				1	20	SPARE	38
39	111 MILE 1727 307					2.6	В	1.0	2	12	1	20	FIRE A LM CNTRL PNL	40
41						3.4	С	1.0	2	12	1	20	FIRE A LM CNTRL PNL	42
TOT	AL DEMAND KVA (PER PHAS	E):	A:	7.6	E	3: 7.5	(C: 8.4	DE	SIGN K	VA:	25	DESIGN AMPS	S: 70

	VOLTAGE: 120 PHASE, WIRE: 3 PH							MAIN	LUGS		(二)	A.I.C.: 10k MOUNTED: SURFAC	Œ
		C/	В	WIF	RE				WIF	RE	C/E	3		Т
CKT	SERVING	Р	TRIP	QTY	AWG	KVA	PH	KVA	QTY	AWG	Р	TRIP	SERVING	CK
1	REC-MED 143	1	20	2	12	8.0	Α	0.8	2	12	1	20	REC-MED 142	2
3	REC-MED 143	1	20	2	12	0.8	В	0.8	2	12	1	20	REC-MED 142	4
5	REC-MED 143	1	20	2	12	0.8	С	0.8	2	12	1	20	REC-MED 142	6
7	REC-MED 143	1	20	2	12	8.0	Α	0.8	3	12	1	20	REC-MED 142	8
9	SUMP PUMP	1	20	2	12	0.8	В	0.8	2	12	1	20	REC-MED 143	10
11	COMM. BKBRD	1	20	2	12	0.8	С	0.8	2	12	1	20	REC-MED 143	12
13	COMM. BKBRD	1	20	2	12	0.8	Α	0.8	2	12	1	20	REC-MED 143	14
15	REC-SIM LAB 120A	1	20	2	12	0.8	В	0.8	3	12	1	20	REC-MED 143	16
17	REC-NUS. SKILLS. 120	1	20	2	12	0.8	C	0.8	2	12	1	20	REC-FACULTY 148	18
19	REC-NUS. SKILLS. 120	1	20	2	12	0.8	Α	0.8	2	12	1	20	REC-FACULTY 148	20
21	REC-NUS. SKILLS. 120	1	20	2	12	0.8	В	0.8	2	12	1	20	REC-FACULTY 148	22
23	REC-NUS. SKILLS. 120	1	20	2	12	0.8	С	0.8	3	12	1	20	REC-FACULTY 148	24
25	REC-NUS. SKILLS. 120	1	20	2	12	0.8	Α	0.8	2	12	1	20	REC-FACULTY 148	26
27	REC-PREP ROOM 120D	1	20	2	12	0.8	В	0.8	2	12	1	20	REC-FACULTY 148	28
29	COUNTER RECP-RM 143	1	20	2	12	0.8	C	0.8	2	12	1	20	REC-FACULTY 148	30
31	COUNTER RECP-RM 142	1	20	2	12	0.8	Α	0.8	3	12	1	20	REC-FACULTY 148	32
33	PROJECTOR RM 143	1	20	2	12	1.0	В	1.0	2	12	1	20	COPIER RM 148	34
35	PROJECTOR RM 142	1	20	2	12	1.0	C	0.7	2	12	1	20	VF#1 & 2	36
37	SPARE	1	20				Α	0.7	2	12	1	20	EF #5,8,910	38
	BUSSED SPACE						В	0.7	2	12	1	20	VF#4 & 6	40
41	BUSSED SPACE						С						BUSSED SPACE	42

* EXISTING ISOLATED GROUND BUS BAR.

	VOLTAGE: 120 / PHASE, WIRE: 3 PH ,					100	AMP	MAIN	LUGS	5			A.I.C.: 10k MOUNTED: SURFAC	Æ
		C	/B	WIF	RE				WIF	RE	C/E	3		Т
CKT	SERVING	Р	TRIP	QTY	AWG	KVA	PH	KVA	QTY	AWG	Р	TRIP	SERV ING	CK
1	REC-CONF. 158A	1	20	2	12	0.8	Α	1.0	2	12	1	20	FAC. RM 147 - DISPOSAL	2
3	REC-CONF. 158A	1	20	2	12	8.0	В	0.4	2	12	1	20	JAN 114 -RECIR. PUMP	4
5	REC-CONF. 158A	1	20	2	12	0.8	С	0.7	2	12	1	20	EF #2	6
7	REC-CONF. 158A	1	20	3	12	0.8	Α	1.0	2	12	1	20	SIGNA GE	8
9	REC-ROOF	1	20	2	12	0.2	В	1.0	2	12	1	20	SIGNA GE	10
11	SYSTEMS FURNITURE (1)	1	20	3	12	0.5	С	1.0	2	12	1	20	SIGNA GE	12
13	SYSTEMS FURNITURE (1)	1	20	3	12	0.5	Α				1	20	SPARE	14
15	SYSTEMS FURNITURE (1)	1	20	3	12	0.5	В				1	20	SPARE	16
17	SYSTEMS FURNITURE (2)	1	20	3	12	0.5	С				1	20	SPARE	18
	SYSTEMS FURNITURE (1)	1	20	3	12	0.5	Α						BUSSED SPACE	20
21	SYSTEMS FURNITURE (1)	1	20	3	12	0.5	В						BUSSED SPACE	22
23	SYSTEMS FURNITURE (1)	1	20	3	12	0.5	С						BUSSED SPACE	24
25	SYSTEMS FURNITURE (2)	1	20	3	12	0.5	Α						BUSSED SPACE	26
1 - 1 - 1	SYSTEMS FURNITURE (1)	1	20	3	12	0.5	В						BUSSED SPACE	28
29	SYSTEMS FURNITURE (1)	1	20	3	12	0.5	С						BUSSED SPACE	30
	SYSTEMS FURNITURE (1)	1	20	3	12	0.5	Α						BUSSED SPACE	32
- CONTRACTOR	SYSTEMS FURNITURE (2)	1	20	3	12	0.5	В						BUSSED SPACE	34
35	REC-COPY 141A (1)	1	20	2	12	0.8	С						BUSSED SPACE	36
37	REC-FAC OFFICE	1	20	2	12	8.0	Α						BUSSED SPACE	38
	REC-COPY 141A (1)	1	20	2	12	0.8	В						BUSSED SPACE	40
41	FIRE A LARM EXTPNL (3)	1	20	2	12	8.0	C						BUSSED SPACE	42

* EXISTING ISOLATED GROUND BUS BAR.

(1) PROVIDE DEDICATED NUETRAL. (2) ISOLATED GROUND CIRCUIT.

(3) PROVIDE HANDLE LOCK-ON CIRCUIT BREAKER COVER.

fax: 410.783.0090 MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc. 757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282

RCG ARCHITECTS

Baltimore, MD 21202 phone: 410.685.7033

Suite 300


509 South Exeter Street

MEDVANCE INSTITUTE
PORT ST. LUCIE
ADMIN/FAC. AREA & SIM SUITE
9164 US Highway 1 South
Port St. Lucie, FL 34928


PROJECT NO: 1225 DATE: 03/18/2013

DRAWING NO:

CONSTRUCTION ISSUE 03/18/2013




* EXISTING ISOLATED GROUND BUS BAR.



OUTLET MOUNTING DETAIL - TYPICAL

NO SCALE

- 1. VERIFY GENERAL PURPOSE OUTLET AND COVER PLATE FINISHES WITH ARCHITECT. COVER PLATES TO BE STAINLESS STEEL OR OTHER STANDARD FINISH AS SELECTED BY THE ARCHITECT.
- 2. LIGHT SWITCHES SHALL MATCH THE GENERAL POWER OUTLET FINISHES.
- 3. OUTLETS FOR PC/COMMUNICATION EQUIPMENT SHALL BE CONNECTED WITH DEDICATED NEUTRAL FOR EACH CIRCUIT. OUTLETS SHALL HAVE GRAY FINISH OR OPPOSITE OF SELECTED GENERAL OUTLET FINISH.



COMMUNICATION RACEWAY DIAGRAM NO SCALE

NOTES:

- 1. BACKBOARD SHALL BE FIRE TREATED PLYWOOD PAINTED MATTE WHITE.
- 2. PROVIDE 3/4" CONDUIT TO FIRE ALARM PANEL, SECURITY PANEL, ATC PANEL & ELEVATOR MACHINE ROOM (WHERE APPLICABLE).

	INTERIOR LIGHTING FIXTURE SCHEDULE												
MADIC	FIXT	URE DES	CRIPTION	DEMARKS	VOLT	MOUNTING	LAMPS		INPUT		TYPICAL		
MARK	ILLUM.	TYPE	DIFFUSER	REMARKS	VOLT	MOUNTING	QTY	TYPE	<u>WATTS</u> EFFICENCY	MANUFACTURER	LOCATION		
D2	COMPACT FLUOR.	DOWN LIGHT	SPECULAR CLEAR ALZAK	VERTICAL LAMP, WIDE BEAM 6" APERTURE, PROVIDE DIMMING BALLAST (NOTE 3)	277	RECESSED	1	32 WATT TRIPLE	35W 60.0%	OMEGA #OM6 SERIES	-		
D3	COMPACT FLUOR.	WALL WASHER	SPECULAR CLEAR ALZAK	6" APERTURE, PROVIDE DIMMING BALLAST (NOTE 3)	277	RECESSED	1	26 WATT TRIPLE		OMEGA #OM6 SERIES	_		
Н1	FLUOR.	2'X2'	SMOOTH	_	277	GRID	2	14W T5	39W 80.6%	LITHONIA #2RT5 SERIES	_		
TL1	COMPACT FLUOR.	TASK LIGHT	I		120	_	1	13W CFL	13W	ERGO (IBIS) #FT13 SERIES	_		
U1	FLUOR.	UNDER CABINET	-	SEE NOTE 4	120	SURFACE MOUNTED	1	_	_	DAYBRITE #MUC SERIES			

INTERIOR LIGHTING NOTES:

- 1. ALL T5 & COMPACT FLUORESCENT FIXTURES TO BE FURNISHED WITH ELECTRONIC BALLAST. PROVIDE MULTI-BALLASTS AND CONNECT FOR DUAL LEVEL LIGHTING WHERE INDICATED ON THE PLANS.
- 2. ALL T5 & COMPACT FLUORESCENT LAMPS TO BE 4100 K, 80 COLOR RENDERING INDEX + U.N.O.
- 3. FIXTURE SHALL BE CAPABLE OF OPERATING 26 WATT OR 32 WATT LAMPS.
- 4. PROVIDE QUANTITY OF 2', 3' AND 4' STRIP LIGHTS REQUIRED FOR LENGTHS INDICATED ON THE PLANS.
- 5. RECESSED LIGHT FIXTURE HOUSING THAT IS IN CONTACT WITH INSULATION SHALL BE IC RATED.

EMERGENCY LIGHTING FIXTURE SCHEDULE											
	DESIG.	FIXTURE DESCRIPTION							LAMPS		TYPICAL
MARK	MARK (NOTE 3)	ILLUM.	TYPE	SOURCE	REMARKS	VOLT	MOUNTING	QTY	TYPE	MANUFACTURER	LOCATION
⊗	EX1	LED	EXIT	INTEGRAL BATTERY	HIGH IMPACT THERMO WHITE PLASTIC HOUSING, SINGLE FACE	277	UNIVERSAL	_	FURNISHED W/ FIXTURE	EMERGI-LITE #PREM SERIES	EXITS
•	EX2	LED	EXIT	INTEGRAL BATTERY	HIGH IMPACT THERMO WHITE PLASTIC HOUSING, DOUBLE FACE	277	UNIVERSAL	_	FURNISHED W/ FIXTURE	EMERGI-LITE #PREM SERIES	EXITS
	EB1	HALOGEN	EMERG.	INTEGRAL BATTERY	TWIN HEAD, NO REMOTE	277	WALL	2	FURNISHED W/ FIXTURE	EMERGI-LITE #PREM SERIES (12V, 12W HEADS)	-

EMERGENCY LIGHTING NOTES:

- 1. EXIT SIGNS SHALL HAVE DIRECTIONAL ARROWS AS INDICATED ON THE PLANS.
- 2. VERIFY COLOR AND CONFIGURATION OF EXIT SIGN LETTERS WITH LOCAL CODES.
- 3. EXIT SIGNS AND EMERGENCY BATTERY PACKS ARE INDICATED BY SYMBOL ON THE PLANS IN LIEU OF LETTER DESIGNATION.
- 4. EXIT SIGNS AND EMERGENCY BATTERY PACKS SHALL BE CONNECTED AHEAD OF LOCAL SWITCH.
- 5. EXIT LIGHTS SHALL BE MOUNTED: (1) ON WALL 6" ABOVE DOOR WHERE POSSIBLE. (2) CEILING MOUNTED. (3) ON WALL TO THE SIDE OF THE DOOR AS HIGH AS POSSIBLE, WHERE CEILING IS TO LOW. EXIT SHALL BE NO MORE THAN 2' HORIZONTALLY FROM THE OPENING. (4) WHEN DEALING WITH HIGH CEILING, I.E. WAREHOUSE, REPAIR BAYS, THE BOTTOM OF THE NEW EGRESS MARKINGS SHALL BE LOCATED AT A VERTICAL DISTANCE OF NOT MORE THAN 80" ABOVE THE TOP EDGE OF THE EGRESS OPENING INTENDED FOR DESIGNATION BY THE MARKING.
- 6. TYPE 'EB1' EMERGENCY LIGHTING SHALL BE WALL MOUNTED AT 7'-0" A.F.F. UNLESS NOTED OTHERWISE.

GENERAL FIXTURE NOTES:

- 1. FIXTURE MARK IS TYPICAL FOR ALL FIXTURES OF THE SAME SYMBOL TYPE WITHIN THE SAME ROOM OR AREA U.N.O.
- 2. FIXTURE CATALOG # ESTABLISHES THE MANUFACTURER'S SERIES # COMPLETE CATALOG # SHALL BE DETERMINED BY THE SCHEDULE DESCRIPTION, PLAN NOTES AND THE SPECIFICATIONS.

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090


MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc. 757 Frederick Road - Suite 300 Catonsville, Maryland 21228 (410) 869-7282

ELECTRICAL SCHEDULES, I AND DIAGRAM

SUIT

PROJECT NO:

1225 DATE: 03/18/2013 DRAWING NO:



GENERAL REQUIREMENTS

- 1. REFER TO THE SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS OF THIS PROJECT.
- 2. <u>BID PHASE:</u>
 IT IS THE CONTRACTOR'S RESPONSIBILITY TO REVIEW ALL DOCUMENTS TO INCLUDE PLANS AND SPECIFICATIONS FOR THE ARCHITECTURAL AND OTHER WORK UNDER OTHER DIVISIONS THAT CAN AFFECT THE WORK OF THIS DIVISION. THE CONTRACTOR SHALL ISSUE A FORMAL REQUEST FOR INFORMATION FOR CLARIFICATIONS OF ANY DISCREPANCIES IN THE DOCUMENTS PRIOR TO FINAL BID SUBMISSION.
- 3. <u>PRE-CONSTRUCTION:</u>
 IT IS THE CONTRACTOR'S RESPONSIBILITY TO REVIEW ALL REVISED DOCUMENTS TO INCLUDE ARCHITECTURAL PLANS AND WORK UNDER OTHER DIVISIONS THAT CAN AFFECT THE WORK OF THIS DIVISION. THIS INCLUDES REVIEW OF ALL ADDENDUMS, REVISIONS AND SHOP DRAWINGS THAT AFFECT THE WORK OF THIS DIVISION. THE CONTRACTOR SHALL NOTIFY THE A/E TEAM OF ANY DISCREPANCIES PRIOR TO FINAL ROUGH—IN.

SPECIAL CONDITIONS

- A. <u>DEMOLITION COORDINATION</u>:
- REFER TO ARCHITECTURAL DEMOLITION PLANS FOR ADDITIONAL DEMOLITION REQUIREMENTS.
- 2. REFER TO ARCHITECTURAL PLANS AND/OR SUPPLEMENTAL DOCUMENTS FOR CONSTRUCTION PHASE SEQUENCE REQUIREMENTS FOR OCCUPIED SPACES AFFECTED BY THE WORK.
- NOTIFY THE LANDLORD OF ANY WORK THAT MAY DISRUPT OTHER AREAS OUTSIDE OF THE WORK AREA.
- B. WORK IN EXISTING CEILINGS:
- 1. REFER TO ARCHITECTURAL CEILING PLAN AND RELATED DETAILS FOR CEILING CONDITIONS, ADDITIONAL REQUIREMENTS, AND SYSTEM INSTALLATION COORDINATION. REFER TO ARCHITECTURAL PLANS FOR AREAS TO BE DEMOLISHED AND PROVIDED WITH NEW CEILING FINISHES. ALL OTHER AREAS ARE EXISTING CEILINGS TO REMAIN.
- 2. WHERE EXISTING CEILING ARE DISTURBED BY THE NEW WORK, THE EXISTING CEILING GRID AND TILES SHALL BE RE-USED AND PROTECTED DURING CONSTRUCTION AND REINSTALLED IN KIND. SECTIONS OF THE CEILING SYSTEM SHALL BE TEMPORARILY REMOVED AND REPLACED IN KIND, WHERE NEEDED, TO ACCOMMODATE THE WORK. DAMAGED CEILING SYSTEMS SHALL BE REPLACED WITH NEW SYSTEMS AS NEEDED.
- EXISTING DISTURBED DRYWALL CEILINGS SHALL BE PATCHED, REPAIRED, AND FINISHED TO MATCH EXISTING CONDITIONS.
- 4. COORDINATE SCOPE OF WORK IN EXISTING CEILINGS WITH GENERAL CONTRACTOR AT TIME OF BIDS AND PRIOR TO START OF WORK.
- C. <u>EQUIPMENT COORDINATION</u>:
- REFER TO ARCHITECTURAL EQUIPMENT PLANS, FURNITURE PLANS, ELEVATIONS, CASEWORK ELEVATIONS AND OTHER RELATED PLANS FOR ADDITIONAL MEP
- D. <u>EXISTING SANITARY WORK</u>:

PROVISIONS.

- CONTRACTOR SHALL VERIFY LOCATION OF EXISTING SANITARY MAINS, SIZES, AND CLEANOUTS IN THE AREA OF NEW PLUMBING WORK.
- 2. VERIFY LOCATION OF NEW TIE IN POINTS TO THE MAIN SANITARY LINE. VERIFICATION WILL INCLUDE DIGGING NECESSARY TEST PITS TO VERIFY LOCATION AND APPROPRIATE DEPTH PRIOR TO COMMENCEMENT OF THE WORK AND TRENCHING NEW LINES
- 3. CONTRACTOR SHALL CONFIRM MAIN LINES ARE CLEAR OF DEBRIS AND FREE FLOWING PRIOR TO TIE—IN WORK.
- 4. CONTRACTOR SHALL PROVIDE AN AS BUILT SKETCH OF THE EXISTING LINES CONFIRMING INVERTS, SIZES, AND DIRECTION OF FALL.

SHEET#	SHEET TITLE
P0.1	COVER SHEET PLUMBING
P1.0	FLOOR PLAN PLUMBING DEMOLITION
P1.1	FLOOR PLAN PLUMBING
P2.1	PLUMBING SCHEDULES AND DETAILS

RCG

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090

Description

Date

MEP ENGINEER:
Siegel, Rutherford, Bradstock & Ridgway, Inc.
757 Frederick Road - Suite 300
Catonsville, Maryland 21228
(410) 869-7282

COVER SHEET
PLUMBING

AREA & SIM SUITE S Highway 1 South Lucie, FL 34928

DMIN/FAC. AREA
9164 US Highway
Port St. Lucie, FL


PROJECT NO:

OF:

1225
DATE: 03/18/2013

SHEET:

PO 1



FLOOR PLAN - PLUMBING DEMOLITION SCALE: 1/4" = 1'-0" 0 1' 2' 4' 8'

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090 MEP ENGINEER:
Siegel, Rutherford, Bradstock & Ridgway, Inc.
757 Frederick Road - Suite 300
Catonsville, Maryland 21228
(410) 869-7282


FLOOR PLAN PLUMBING DEMOLITION


MEDVANCE INSTITUTE
PORT ST. LUCIE
ADMIN/FAC. AREA & SIM SUITE
9164 US Highway 1 South
Port St. Lucie, FL 34928


PROJECT NO: **1225**

OF:

DATE: 03/18/2013 DRAWING NO:









TRAPEZE PIPE SUPPORT DETAIL NO SCALE

PIPE SUPPORT DETAIL NO SCALE

	PLUMBING FIXTURE SCHEDULE										
DESIG	FIXTURE TYPE	HW	CW	SAN	SPECIFICATIONS						
P-1A	COUNTERTOP SINK SINGLE BOWL	<i>y</i> ₂ "	1/2"	2"	"ELKAY" No. 'LRAD—2522': (25"x22"x6") 18 GAUGE STAINLESS STEEL SELF—RIM TYPE, 4" CENTERS, OFF—CENTERED DRAIN, ADA COMPLIANT. FURNISH FAUCET No. 'LK2445BH' WITH HI—ARC SPOUT AND WING HANDLES AND CRUMB CUP STRAINER No 'LK—35'. PROVIDE SUPPLIES WITH STOPS AND 'P'—TRAP.						



NO SCALE



WATER RISER DIAGRAM

NO SCALE

CONSTRUCTION ISSUE 03/18/2013

SRBR No: 13039

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090


MEP ENGINEER:
Siegel, Rutherford, Bradstock & Ridgway, Inc.
757 Frederick Road - Suite 300
Catonsville, Maryland 21228
(410) 869-7282

PLUMBING
SCHEDULES
DETAILS

SUITE

PROJECT NO:

1225 DATE: 03/18/2013 DRAWING NO:



FIRE ALARM SYMBOLS <u>SYMBOL</u> **DESCRIPTION** FIRE ALARM SYSTEM MANUAL PULL STATION. 48" A.F.F. FIRE ALARM SYSTEM VISUAL (STROBE) DEVICE. WALL MOUNTED 80" A.F.F. CANDELLA RATING PER NFPA 72, U.N.O. FIRE ALARM SYSTEM COMBINATION (HORN/ STROBE) AUDIBLE/ VISUAL DEVICE. WALL MOUNTED 80" AFF; CANDELLA RATING PER NFPA 72, U.N.O. FIRE ALARM SYSTEM SMOKE DETECTOR FIRE ALARM SYSTEM PANEL - 'FACP' DESIGNATES FIRE ALARM CONTROL PANEL, SURFACE MOUNTED; 'FAAP' DESIGNATES FIRE ALARM ANNUNCIATOR PANEL, RECESSED 1. DUCT SMOKE DETECTOR FURNISHED UNDER DIVISION 16, INSTALLED UNDER DIVISION 15 AND WIRED

- UNDER DIVISION 16. ALL ROOF TOP UNITS OF 2000 CFM AND LARGER SHALL HAVE DUCT SMOKE DETECTORS IN THE SUPPLY AND RETURNS OF EACH ROOF TOP UNIT, AS REQUIRED BY AUTHORITY HAVING JURISDICTION.
- 2. NUMBER ADJACENT TO VISUAL SIGNALING DEVICE INDICATES CANDELA RATING OF DEVICE.
- 3. DIVISION 15 SHALL FURNISH AND INSTALL ALL FIRE SMOKE DAMPERS AND FIRE DAMPERS. SMOKE DAMPERS SHALL BE PROVIDED WITH DUCT SMOKES BY DIVISION 15. ALL REQUIRED POWER AND CONTROL WIRING, TRANSFORMERS, ACTUATORS, RELAYS, MODULES AND OTHER COMPONENTS TO BE FURNISHED AND INSTALLED BY DIVISION 15. DIVISION 16 SHALL MONITOR THE SMOKE DAMPERS VIA THE FIRE ALARM SYSTEM. DIVISION 16 TO PROVIDE COMPONENTS AND WIRING AS REQUIRED TO MONITOR FIRE SMOKE DAMPERS.
- 4. DIVISION 16 TO PROVIDE ALL WIRING, RELAYS, MODULES, TRANSFORMERS REQUIRED TO CONNECT ALL SMOKE DAMPERS TO THE FIRE ALARM SYSTEM. SEE MECHANICAL AND ARCHITECTURAL DRAWINGS TO CONFIRM QUANTITY AND LOCATIONS OF SMOKE AND FIRE DAMPERS.

#17 (E) SMOKE DETECTOR (E) -MAIN FIRE ALARM CONNECT TO MAIN FIRE CONTROL PANEL (E) ALARM CONTROL PANEL AS REQUIRED (TYPICAL)— $\nabla \wedge \nabla - \nabla$ FIRE HORNS INITIATION DEVICES F+F-EXTENDER PANEL IF REQUIRED (NOTE 1) REFER TO DRAWINGS FOR ADDITIONAL DEVICES AND LOCATIONS ----└─ P1H-41

FIRE ALARM RISER DIAGRAM NO SCALE

1. PROVIDE EXTENDER/BOOSTER PANEL IF NEEDED FOR ADDITIONAL STROBE CIRCUITS. PROVIDE 120 VOLT POWER CONNECTION

GENERAL REQUIREMENTS

- 1. REFER TO THE SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS OF THIS PROJECT.
- IT IS THE CONTRACTOR'S RESPONSIBILITY TO REVIEW ALL DOCUMENTS TO INCLUDE PLANS AND SPECIFICATIONS FOR THE ARCHITECTURAL AND OTHER WORK UNDER OTHER DIVISIONS THAT CAN AFFECT THE WORK OF THIS DIVISION. THE CONTRACTOR SHALL ISSUE A FORMAL REQUEST FOR INFORMATION FOR CLARIFICATIONS OF ANY DISCREPANCIES IN THE DOCUMENTS PRIOR TO FINAL BID SUBMISSION.
- IT IS THE CONTRACTOR'S RESPONSIBILITY TO REVIEW ALL REVISED DOCUMENTS TO INCLUDE ARCHITECTURAL PLANS AND WORK UNDER OTHER DIVISIONS THAT CAN AFFECT THE WORK OF THIS DIVISION. THIS INCLUDES REVIEW OF ALL ADDENDUMS, REVISIONS AND SHOP DRAWINGS THAT AFFECT THE WORK OF THIS DIVISION. THE CONTRACTOR SHALL NOTIFY THE A/E TEAM OF ANY DISCREPANCIES PRIOR TO FINAL ROUGH-IN.

SPECIAL CONDITIONS

- A. <u>DEMOLITION COORDINATION:</u>
- 1. REFER TO ARCHITECTURAL DEMOLITION PLANS FOR ADDITIONAL DEMOLITION REQUIREMENTS.
- 2. REFER TO ARCHITECTURAL PLANS AND/OR SUPPLEMENTAL DOCUMENTS FOR CONSTRUCTION PHASE SEQUENCE REQUIREMENTS FOR OCCUPIED SPACES AFFECTED
- 3. NOTIFY THE LANDLORD OF ANY WORK THAT MAY DISRUPT OTHER AREAS OUTSIDE OF THE WORK AREA.
- B. WORK IN EXISTING CEILINGS:
- 1. REFER TO ARCHITECTURAL CEILING PLAN AND RELATED DETAILS FOR CEILING CONDITIONS, ADDITIONAL REQUIREMENTS, AND SYSTEM INSTALLATION COORDINATION. REFER TO ARCHITECTURAL PLANS FOR AREAS TO BE DEMOLISHED AND PROVIDED WITH NEW CEILING FINISHES. ALL OTHER AREAS ARE EXISTING CEILINGS TO REMAIN.
- 2. WHERE EXISTING CEILING ARE DISTURBED BY THE NEW WORK, THE EXISTING CEILING GRID AND TILES SHALL BE RE-USED AND PROTECTED DURING CONSTRUCTION AND REINSTALLED IN KIND. SECTIONS OF THE CEILING SYSTEM SHALL BE TEMPORARILY REMOVED AND REPLACED IN KIND. WHERE NEEDED. TO ACCOMMODATE THE WORK. DAMAGED CEILING SYSTEMS SHALL BE REPLACED WITH NEW SYSTEMS AS NEEDED.
- 3. EXISTING DISTURBED DRYWALL CEILINGS SHALL BE PATCHED, REPAIRED, AND FINISHED TO MATCH EXISTING CONDITIONS.
- 4. COORDINATE SCOPE OF WORK IN EXISTING CEILINGS WITH GENERAL CONTRACTOR AT TIME OF BIDS AND PRIOR TO START OF WORK.
- C. SPRIN<u>KLER_SYSTEM</u>:

FLOOR PLAN FIRE PROTECTION

- 1. PROTECT AND MAINTAIN EXISTING SPRINKLER SYSTEM DURING DEMOLITION AND CONSTRUCTION.
- 2. COORDINATE TEMPORARY DISRUPTIONS WITH THE LANDLORD.
- 3. REWORK EXISTING SPRINKLER SYSTEM TO NEW FINISHED CEILING PER NFPA REQUIREMENTS.
- 4. REFER TO ARCHITECTURAL, CEILING PLAN, LIGHTING PLAN, AND HVAC PLAN FOR COORDINATION.

DISCREPANCIES WITH EQUIPMENT PROVISIONS PRIOR TO ROUGH-IN.

- 5. IT IS THE CONTRACTOR'S RESPONSIBILITY TO REVIEW ALL DOCUMENTS AND THE EXISTING CONDITIONS PRIOR TO START OF WORK. NOTIFY THE ENGINEER OF ANY
- 6. CONTRACTOR TO INCLUDE IN BID PROPOSAL ALL OFF HOURS WORK AS REQUIRED SO AS NOT TO INTERRUPT TENANT'S DAY TO DAY OPERATION.

DRAWING LIST								
SHEET #	SHEET TITLE							
FP0 1	COVER SHEET FIRE PROTECTION							

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033


fax: 410.783.0090


MEP ENGINEER: Siegel, Rutherford, Bradstock & Ridgway, Inc.

Catonsville, Maryland 21228

CO FIRE SU

PROJECT NO:





FLOOR PLAN - FIRE PROTECTION

SIM LABS SCALE: 1/4" = 1'-0" 0 1' 2' 4' 8'

GENERAL NOTES:

- ALL FIRE PROTECTION EQUIPMENT AND DEVICES SHOWN
 ARE NEW UNLESS NOTED OTHERWISE.
- ALL NEW FIRE PROTECTION EQUIPMENT AND DEVICE TO MATCH EXISTING.
- 3. EXISTING FIRE PROTECTION EQUIPMENT AND DEVICES ARE SHOWN FOR REFERENCE PURPOSES ONLY.

FIRE PROTECTION PLAN NOTES:

- F1 PROVIDE NEW ADA APPROVED FIRE ALARM STROBE. MAKE CONNECTION TO EXISTING SYSTEMS AS REQUIRED.
- F2 PROVIDE NEW ADA APPROVED COMBINATION FIRE ALARM HORN/STROBE. MAKE CONNECTION TO EXISTING SYSTEMS AS REQUIRED.
- F3 EXISTING FIRE ALARM STROBE TO BE REMOVED. REMOVE ALL ASSOCIATED WIRING BACK TO SOURCE PANEL.
- F4 EXISTING SMOKE DETECTOR TO BE REMOVED. REMOVE ALL ASSOCIATED WIRING BACK TO SOURCE PANEL.

EXISTING CONDITIONS

DESIGNATION

(N) NEW EQUIPMENT

(N) NEW EQUIPMENT(E) EXISTING EQUIPMENT TO REMAIN(R) EXISTING EQUIPMENT RELOCATED

CONSTRUCTION ISSUE 03/18/2013

EXISTING EQUIPMENT TO BE REMOVED

SRBR No: 13039

RCG

RCG ARCHITECTS 509 South Exeter Street Suite 300 Baltimore, MD 21202 phone: 410.685.7033 fax: 410.783.0090

Date Description

MEP ENGINEER:
Siegel, Rutherford, Bradstock & Ridgway, Inc.
757 Frederick Road - Suite 300
Catonsville, Maryland 21228
(410) 869-7282

PPROVAL

PLAN ROTECTION 3S

FLOOR PLAN
FIRE PROTECT
SIM LABS

ORT ST. LUCIE
C. AREA & SIM SUITE
4 US Highway 1 South
rt St. Lucie, FL 34928

MEDVANCE INS
PORT ST. LU
DMIN/FAC. AREA
9164 US Highway
Port St. Lucie, FL

PROJECT NO:

1225

DATE: 03/18/2013

DRAWING NO:

FP1.1

OF: